

Attn: MS Sue Schultz
m/s Beaulieu of Australia
64 Lahrs Rd, Ormeau Q/Ld 4208

LABORATORY TEST REPORT
P178191A

TUSCAN SUN

Sample description as provided by customer

Pile weight mass/unit area 30 oz/yd²

Construction Details Tufted Secondary Backing Synthetic

Style Cut Pile

Order No. 28238

Pile Fibre Content 100% RESISTAIN SOLUTION DYED NYLON

Colour Shell

Pile Height mm

TEST METHOD: AS.ISO 9239.1 2003 Reaction To Fire Tests For Floorings Part 1 Determination of the Burning Behaviour Using a Radiant Heat Source. As required by the Building Code of Australia (BCA) and National Construction Code 2015 (NCC) specifications C1.10. Sample conditioning as specified in BS EN 13238.2010.

Sample Submitted Date Jul 2017

Test Date July 2017

Total Thickness mm

Assembly System: OVER UNDERLAY AIRSTEP BLACK RUBBER.

The UNDERLAY used was AIRSTEP BLACK RUBBER.

Substrate: Non-Combustible - 6mm Fibre Reinforced Cement Board to simulate a Non-Combustible Flooring.
The Holding Torque on Specimen Frame was 2Nm.

The standard requires two Initial Tests be conducted on samples mounted in both Length and Width directions. Two further samples are then tested in whichever direction has the lowest Critical Radiant Flux.

Initial Tests: Length Direction Critical Radiant Flux 2.4 kW/m²
Width Direction Critical Radiant Flux 2.4 kW/m²

	Specimen Tests conducted in the Length Direction			
	Specimen #1	Specimen #2	Specimen #3	Mean
Critical Radiant Flux (kW/m ²)	2.4	2.4	2.1	2.3
Smoke Development Rate (%.min)	254	266	271	264

The values quoted below are as required by BCA and NCC Specification C1.10 Fire Hazard Properties (Floors).
The Critical Radiant Flux quoted is the value at Flame-Out/Extinguishment (BCA General Provisions A1.1).

Mean Critical Radiant Flux **2.3** kW/m²

Mean Smoke Development Rate **264** %.min

Observations: The samples shrunk away from the heat source, ignited and burnt.

AS.ISO 9239.1 Clause 9(o) The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use.

All information required for compliance with the BCA and NCC is given on this test report page.

Page 1 of 2

(v5-0, 11/03/2017)



ACCREDITED FOR
TECHNICAL
COMPETENCE

M. B. Webb
Technical Manager

DATE: 31/7/2017

Performance & Approvals
Accreditation No. 15393
Accredited for compliance with ISO/IEC 17025.

TIME FOR EACH SPECIMEN TO REACH EACH MARKER IN SECONDS

Specimen	50	60	110	160	210	260	310	360	410	460	510	560	610	660	710	760	810	860
1	170	171	229	241	293	334	359	448	483	605	990	1624						
2	183	184	239	248	301	347	551	628	793	885	1246	1894						
3	199	200	235	294	382	453	539	674	865	939	1299	1652	1943					

TESTS

BURNING CHARACTERISTICS

SMOKE PRODUCTION

Specimen	Burn Length (mm) at Flame Out/ Extinguishment	Time To Burn Out (s)	Maximum Light Attenuation (%)	Smoke Development Rate (%.min)
Initial Test: Width	603	1,985	58	267
Specimen Tests: Length				
1	605	1,877	59	254
2	607	2,136	57	266
3	647	2,296	58	271
Mean	620	2,103	58	264



ACCREDITED FOR
**TECHNICAL
COMPETENCE**

M. B. Webb
Technical Manager

DATE: 31/7/2017

Performance and Approvals
Accreditation No. 15393
Accredited for compliance
with ISO/IEC 17025.

2004 04 09

31 July 2017